



11. ruj 2026. 09:06:12



11. ruj 2026. 09:06:17



11. ruj 2026. 09:07:07



11. ruj 2026. 09:07:31



11. ruj 2026. 09:08:00



11. ruj 2026. 09:08:22





11. ruj 2026. 09:09:49



11. ruj 2026. 09:10:19





洛阳北玻三元流风机技术有限公司

LUOYANG NORTH GLASS TRITURBO FAN TECHNOLOGY CO., LTD.

风 量 FLOW	m ³ /h	功 率 POWER	250 kW
风 压 PRESSURE	Pa	转 速 ROTATION SPEED	1450 RPM
型 号 TYPE	XTFIII-14a-D-R0°	风机编号 FAN NO.	FJ202311100040
前 轴 承 FRONT BEARING	22222/C3	后 轴 承 BACK BEARING	22222/C3
生产日期 DATE	2023/12	介质温度 MEDIUM TEMP	20 °C
TEL:0379-63310692 0379-69920614(售后)			



11. ruj 2026. 09:12:29



11. ruj 2026. 09:15:27



11. ruj 2026. 09:15:32



11. ruj 2026. 09:15:36

HORIZONTAL ROLLER HEARTH GLASS TEMPERING FURNACE

GENERAL DATA

ELECTRICAL PARAMETERS

PERFORMANCE DATA

TYPE NO.	RD-1036	POWER SUPPLY	AC	V	Hz	Hz	Hz	Hz	Hz
MODEL NO.	CW238957	POWER HEAT (kW)							
TYPE NO.	45000	10 TON LONG CURRENT							
MODEL NO.	18.6X402.8	10 TON LONG CURRENT							
MODEL NO.	-20	90							
MODEL NO.	500								
MODEL NO.	30	90							
MODEL NO.	2027-11								

200

HORIZONTAL ROLLER HEARTH GLASS TEMPERING FURNACE

GENERAL DATA		ELECTRICAL PARAMETERS		PNEUMATICS DATA	
TYPE NO.	AU-1036	POWER SUPPLY	AC 400V-50Hz, 3P/ N / PE	WORKING PRESSURE	0.6
SERIAL NO.	CR230937	POWER INPUT (MAX.)	680 kVA	FLUID	8
TOTAL WEIGHT	45000 kg	FULL-LOAD CURRENT	967 A	TANK CAPACITY	2
OUTLINE SIZE	18.5X4X2.8 m	INTERRUPTING CAPACITY	30 kA	* READ INSTRUCTIONS BEFORE USE * FOR INDUCTION ONLY * BULK CEMENT MUST BE STORED IN DRY PLACE TO AVOID MOISTURE * THIS EQUIPMENT MUST BE MAINTAINED	
AMBIENT TEMP	-20 ~ 40 °C	CAPACITY			
ALTITUDE	≤ 500 m	LENGTH	300 ~ 3660 mm		
HUMIDITY	30 ~ 95 %	WIDTH	100 ~ 2100 mm		
PRODUCTION DATE	2023.11	THICKNESS	4 ~ 19 mm		

